RS04

High technology and innovative upgrades set the industry benchmark

Power Your Home

www.rippa.com

Kubota Z482 engine



Triple gear pump system



Hydraulic oil cooler, rapid cooling to protect the hydraulic system







Five auxiliary hydraulic circuits




One machine, multiple functions: Supports dozens of attachments




Universal quick-coupler interface, enables attachment change in 30 seconds, improving efficiency

PARAMETER

www.rippa.com





Unit: mm

Basic parameters	Machine operating weight	930kg	2050 lb
	Bucket capacity	0.15m³	5.3 ft³
	Rated load capacity (safe load)	240kg	529.1 lb
	Maximum load mass	480kg	1058.2 lb
	Travel speed (low/high speed)	0-2.5km/h	0-1.55mph
	Gradeability	25%	25%
	Ground pressure	25.17kpa	3.7psi
	Maximum discharge height	1553mm	61.2in
	Maximum loading height	2080mm	82.0in
	Maximum discharge distance	550mm	21.7in
	Minimum ground clearance	108mm	4.3in
Engine	Engine Brand	Kubota	Kubota
	Engine Model	Z482	Z482
	Max. Horsepower	11.7hp	11.54ps
	Max. Power	8.2kw	11hp
	Max. Speed	3000rpm	3000rpm
	Displacement	0.479L	0.127gal
	Number of Cylinders	2	2
	Cooling Method	Water cooling	Water cooling
	Engine Oil Capacity	2.5L	0.66gal
	Fuel Type	Diesel	Diesel
	Fuel Grade	0/-10	0/-10
	Theoretical Fuel Consumption	0.8-1.2L/h	0.21-0.32gal

Body	Transport length with bucket (mm)	1970mm	77.6in
	Transport length without bucket (mm)	1520mm	59.8in
	Transport width (mm)	1150mm	45.3in
	Transport height (mm)	1300mm	51.2in
	Bucket width (mm)	1150mm	45.3in
Hydraulic system	Main pump type/model	Gear pump PGP64422H92	Gear pump PGP64422H92
	Main pump brand	Tianjin Walking	Tianjin Walking
	Maximum main pump flow rate	18+12+12L/min	4.8+3.2+3.2gpm
	Multi-way valve - Left	Double-way multiport valve	Double-way multiport valve
	Multi-way valve brand	Tengfei	Tengfei
	Multi-way valve - Center	Double-way multiport valve	Double-way multiport valve
	Multi-way valve brand	Tengfei	Tengfei
	Multi-way valve - Right	Double-way multiport valve	Double-way multiport valve
	Multi-way valve brand	Tengfei	Tengfei
	Working pressure setting	14.5MPa	2103psi
	Travel pressure setting	14.5MPa	2103psi
	Travel hydraulic motor type	Deston BM5-315	Deston BM5-315
	Travel motor brand	Deston	Deston
	Motor displacement	315	315

SCENARIO APPLICATION

The RIPPA RS04, a compact stand-on skid steer loader, offers an excellent power-to-weight ratio in an ultra-compact body. It is especially suitable for working in low-ceilinged sheds, agricultural facilities with limited space, and small projects that require economical and efficient solutions.

Dealer / Name:

WhatsApp / Phone:

Address:

Email: